




DATASHEET

axE2-4950



Wi-Fi 6

IEEE 802.11 a/n/ac/ax
2x2 MU-MIMO
MiniPCIe Radio Module



High Performance

30 dBm TX Power
4.9 GHz to 5.9 GHz



Industrial grade

-40 deg C to +85 deg C
operation temperature



VIZMONET PTE LTD

21 Woodlands Close, #03-01, Primz Biz Hub, Singapore 737 854
+65 6255 0581 | enquiry@vizmonet.com | <https://vizmonet.com>

HW REV# axE24950.0200
Last updated on May-18-2025

CUSTOM DESIGN (Options)

Heatsink, Shield Cover and Mechanical Parts

Talk to our experts



enquiry@vizmonet.com



TECHNICAL SPECIFICATION

RADIO MODULE – GENERAL INFO	
Chipset	QUALCOMM QCN-9072-1
EEPROM	2-Mbit serial I ² C bus EEPROM
Host Interface	Mini PCIe interface with PCIe 3.0
Operating System	Linux, supports open source ath11K Linux driver
Security	AES-CCMP at 128/256 bits AES-GCMP at 128/256 bits WEP, TKIP hardware encryption WAPI-2 hardware encryption WPA/WPA2-Personal/WPA2-Enterprise and WPA3 Personal
Operating frequency (11b/g/n)	4900 MHz to 5900 MHz
Data rate-11a	6Mbps, 9Mbps, 12Mbps, 18 Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps
Data rate-11n	MCS0, MCS1, MCS2, MCS3, MCS4, MCS5, MCS6, MCS7
Data rate-11ac	MCS0, MCS1, MCS2, MCS3, MCS4, MCS5, MCS6, MCS7, MCS8, MCS9, MCS10, MCS11
Data rate-11ax	MCS0, MCS1, MCS2, MCS3, MCS4, MCS5, MCS6, MCS7, MCS8, MCS9, MCS10, MCS11, MCS12, MCS13
Channel BW	5 MHz/10 MHz/20 MHz/40 MHz/80 MHz/160 MHz
Compliance	RoHS, MIL-STD-810G Shock & Vibration
MAC ID	848D84 Series
INTERFACE SPECIFICATIONS	
Operating Voltage	3.3V DC / 5V DC (through miniPCI pins 45,47,49,51 for PA)
Total DC Power Consumption	9.5 Watts in 2x2 MIMO mode
RF Antenna connector	x2 MMCX Female(Jack), Straight connectors
ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature Range	-40 deg C to +85 deg C
PHYSICAL SPECIFICATIONS	
Mechanical Dimension	(L) 51 mm x (W) 30 mm x (H) 25.5mm
Weight (grams)	50
REGULATORY INFORMATION	
Compliance	Work in Progress
PACKAGING INFORMATION	
No of units	50, Shipping Carton Dimension (52 cm x 23 cm x 13 cm)

ORDERING INFORMATION

axE2-4950

Mini PCIe Radio Module, 2x2 MU-MIMO, IEEE 802.11 a/n/ac/ax, 4.9/5 GHz
30 dBm

RADIO SPECIFICATION

TX Power per chain (SISO mode), ± 2 dBm.

DC power consumption is the total dc power drawn only by the miniPCIe module in 2x2 MIMO mode and it excludes the dc power drawn by the main board to which the module is connected.

RX Sensitivity per chain (SISO mode) , ± 2 dBm.

TX/RX Specification (11a) – 4920 MHz to 4990 MHz

Data Rate	Modulation	TX Power (dBm)	DC Power Consumption (Watts)	RX Sensitivity (dBm)
6 Mbps	BPSK	27	9.5	-94
9 Mbps	BPSK	27	9.5	-92
12 Mbps	QPSK	25	7	-91
18 Mbps	QPSK	24	6.7	-90
24 Mbps	16-QAM	22	6	-85
36 Mbps	16-QAM	21	5.7	-82
48 Mbps	64-QAM	21	5.7	-77
54 Mbps	64-QAM	20	5.3	-76

TX/RX Specification (11a) – 51800 MHz to 5825 MHz

Data Rate	Modulation	TX Power (dBm)	DC Power Consumption (Watts)	RX Sensitivity (dBm)
6 Mbps	BPSK	27	9.5	-94
9 Mbps	BPSK	27	9.5	-92
12 Mbps	QPSK	26	9	-91
18 Mbps	QPSK	25	7	-90
24 Mbps	16-QAM	25	7	-85
36 Mbps	16-QAM	23	6.3	-82
48 Mbps	64-QAM	22	6	-77
54 Mbps	64-QAM	21	5.7	-76

TX/RX Specification (11n) – 4920 MHz to 4990 MHz

TX Power per chain (SISO mode), ± 2 dBm.

DC power consumption is the total dc power drawn only by the miniPCle module in 2x2 MIMO mode and it excludes the dc power drawn by the main board to which the module is connected.

RX Sensitivity per chain (SISO mode), ± 2 dBm.

Data Rate	Modulation	TX Power (dBm)	DC Power Consumption (Watts)	RX Sensitivity (dBm)
HT20-MCS0	BPSK	27	9.5	-92
HT20-MCS1	QPSK	26	9	-89
HT20-MCS2	QPSK	23	6.3	-87
HT20-MCS3	16-QAM	22	6	-83
HT20-MCS4	16-QAM	21	5.7	-80
HT20-MCS5	64-QAM	20	5.3	-76
HT20-MCS6	64-QAM	19	5	-74
HT20-MCS7	64-QAM	19	5	-73
HT40-MCS0	BPSK	27	9.5	-89
HT40-MCS1	QPSK	26	9	-86
HT40-MCS2	QPSK	23	6.3	-84
HT40-MCS3	16-QAM	22	6	-80
HT40-MCS4	16-QAM	21	5.7	-77
HT40-MCS5	64-QAM	20	5.3	-73
HT40-MCS6	64-QAM	19	5	-71
HT40-MCS7	64-QAM	19	5	-70

TX/RX Specification (11n) – 5180 MHz to 5825 MHz

TX Power per chain (SISO mode), ± 2 dBm.

DC power consumption is the total dc power drawn only by the miniPCle module in 2x2 MIMO mode and it excludes the dc power drawn by the main board to which the module is connected.

RX Sensitivity per chain (SISO mode), ± 2 dBm.

Data Rate	Modulation	TX Power (dBm)	DC Power Consumption (Watts)	RX Sensitivity (dBm)
HT20-MCS0	BPSK	27	9.5	-92
HT20-MCS1	QPSK	26	9	-89
HT20-MCS2	QPSK	25	7	-87
HT20-MCS3	16-QAM	24	6.7	-83
HT20-MCS4	16-QAM	23	6.3	-80
HT20-MCS5	64-QAM	22	6	-76
HT20-MCS6	64-QAM	21	5.7	-74
HT20-MCS7	64-QAM	21	5.7	-73
HT40-MCS0	BPSK	27	9.5	-89
HT40-MCS1	QPSK	27	9.5	-86
HT40-MCS2	QPSK	26	9	-84
HT40-MCS3	16-QAM	25	7	-80
HT40-MCS4	16-QAM	24	6.7	-77
HT40-MCS5	64-QAM	23	6.3	-73
HT40-MCS6	64-QAM	22	6	-71
HT40-MCS7	64-QAM	21	5.7	-70

TX/RX Specification (11ac) – 4920 MHz to 4990 MHz

TX Power per chain (SISO mode), ± 2 dBm.

DC power consumption is the total dc power drawn only by the miniPCle module in 2x2 MIMO mode and it excludes the dc power drawn by the main board to which the module is connected.

RX Sensitivity per chain (SISO mode), ± 2 dBm.

Data Rate	Modulation	TX Power (dBm)	DC Power Consumption (Watts)	RX Sensitivity (dBm)
VHT20-MCS0	BPSK	27	9.5	-95
VHT20-MCS1	QPSK	26	9	-93
VHT20-MCS2	QPSK	23	6.3	-91
VHT20-MCS3	16-QAM	22	6	-88
VHT20-MCS4	16-QAM	21	5.7	-84
VHT20-MCS5	64-QAM	20	5.3	-80
VHT20-MCS6	64-QAM	19	5	-79
VHT20-MCS7	64-QAM	19	5	-78
VHT20-MCS8	256-QAM	19	5	-73
VHT20-MCS9	256-QAM	18	5	-71
VHT20-MCS10	1024-QAM	18	5	-68
VHT20-MCS11	1024-QAM	18	5	-66
VHT40-MCS0	BPSK	27	9.5	-86
VHT40-MCS1	QPSK	26	9	-84
VHT40-MCS2	QPSK	23	6.3	-82
VHT40-MCS3	16-QAM	21	5.7	-79
VHT40-MCS4	16-QAM	21	5.7	-75
VHT40-MCS5	64-QAM	20	5.3	-71
VHT40-MCS6	64-QAM	19	5	-70
VHT40-MCS7	64-QAM	19	5	-69
VHT40-MCS8	256-QAM	19	5	-64
VHT40-MCS9	256-QAM	18	5	-62
VHT40-MCS10	1024-QAM	18	5	-59
VHT40-MCS11	1024-QAM	18	5	-57

TX/RX Specification (11ac) – 5180 MHz to 5825 MHz

TX Power per chain (SISO mode), ± 2 dBm.

DC power consumption is the total dc power drawn only by the miniPCle module in 2x2 MIMO mode and it excludes the dc power drawn by the main board to which the module is connected.

RX Sensitivity per chain (SISO mode), ± 2 dBm.

Data Rate	Modulation	TX Power (dBm)	DC Power Consumption (Watts)	RX Sensitivity (dBm)
VHT20-MCS0	BPSK	27	9.5	-89
VHT20-MCS1	QPSK	26	9	-87
VHT20-MCS2	QPSK	25	7	-85
VHT20-MCS3	16-QAM	24	6.7	-82
VHT20-MCS4	16-QAM	23	6.3	-78
VHT20-MCS5	64-QAM	22	6	-74
VHT20-MCS6	64-QAM	21	5.7	-73
VHT20-MCS7	64-QAM	21	5.7	-72
VHT20-MCS8	256-QAM	20	5.3	-67
VHT20-MCS9	256-QAM	20	5.3	-65
VHT20-MCS10	1024-QAM	19	5	-62
VHT20-MCS11	1024-QAM	19	5	-60
VHT40-MCS0	BPSK	27	9.5	-86
VHT40-MCS1	QPSK	26	9	-84
VHT40-MCS2	QPSK	25	7	-82
VHT40-MCS3	16-QAM	24	6.7	-79
VHT40-MCS4	16-QAM	23	6.3	-75
VHT40-MCS5	64-QAM	22	6	-71
VHT40-MCS6	64-QAM	21	5.7	-70
VHT40-MCS7	64-QAM	21	5.7	-69
VHT40-MCS8	256-QAM	20	5.3	-64
VHT40-MCS9	256-QAM	20	5.3	-62
VHT40-MCS10	1024-QAM	19	5	-59
VHT40-MCS11	1024-QAM	19	5	-57

TX/RX Specification (11ac) – 5180 MHz to 5825 MHz

TX Power per chain (SISO mode), ± 2 dBm.

DC power consumption is the total dc power drawn only by the miniPCle module in 2x2 MIMO mode and it excludes the dc power drawn by the main board to which the module is connected.

RX Sensitivity per chain (SISO mode) , ± 2 dBm.

Data Rate	Modulation	TX Power (dBm)	DC Power Consumption (Watts)	RX Sensitivity (dBm)
VHT80-MCS0	BPSK	27	9.5	-89
VHT80-MCS1	QPSK	25	7	-87
VHT80-MCS2	QPSK	25	7	-85
VHT80-MCS3	16-QAM	24	6.7	-82
VHT80-MCS4	16-QAM	23	6.3	-78
VHT80-MCS5	64-QAM	23	6.3	-74
VHT80-MCS6	64-QAM	22	6	-73
VHT80-MCS7	64-QAM	21	5.7	-72
VHT80-MCS8	256-QAM	21	5.7	-67
VHT80-MCS9	256-QAM	20	5.3	-65
VHT80-MCS10	1024-QAM	19	5	-62
VHT80-MCS11	1024-QAM	19	5	-60
VHT160-MCS0	BPSK	27	9.5	-86
VHT160-MCS1	QPSK	25	7	-84
VHT160-MCS2	QPSK	24	6.7	-82
VHT160-MCS3	16-QAM	23	6.3	-79
VHT160-MCS4	16-QAM	22	6	-75
VHT160-MCS5	64-QAM	22	6	-71
VHT160-MCS6	64-QAM	21	5.7	-70
VHT160-MCS7	64-QAM	21	5.7	-69
VHT160-MCS8	256-QAM	20	5.3	-64
VHT160-MCS9	256-QAM	20	5.3	-62
VHT160-MCS10	1024-QAM	18	5	-59
VHT160-MCS11	1024-QAM	18	5	-57

TX/RX Specification (11ax) – 4920 MHz to 4990 MHz

TX Power per chain (SISO mode), ± 2 dBm.

DC power consumption is the total dc power drawn only by the miniPCle module in 2x2 MIMO mode and it excludes the dc power drawn by the main board to which the module is connected.

RX Sensitivity per chain (SISO mode), ± 2 dBm.

Data Rate	Modulation	TX Power (dBm)	DC Power Consumption (Watts)	RX Sensitivity (dBm)
HE20-MCS0	BPSK	27	9.5	-93
HE20-MCS1	QPSK	26	9	-92
HE20-MCS2	QPSK	23	6.3	-90
HE20-MCS3	16-QAM	22	6	-88
HE20-MCS4	16-QAM	21	5.7	-84
HE20-MCS5	64-QAM	20	5.3	-80
HE20-MCS6	64-QAM	19	5	-78
HE20-MCS7	64-QAM	19	5	-76
HE20-MCS8	256-QAM	18	5	-73
HE20-MCS9	256-QAM	18	5	-71
HE20-MCS10	1024-QAM	17	5	-68
HE20-MCS11	1024-QAM	17	5	-65
HE20-MCS12	4096-QAM	16	5	-64
HE20-MCS13	4096-QAM	16	5	-63
HE40-MCS0	BPSK	27	9.5	-90
HE40-MCS1	QPSK	26	9	-89
HE40-MCS2	QPSK	23	6.3	-87
HE40-MCS3	16-QAM	22	6	-85
HE40-MCS4	16-QAM	21	5.7	-81
HE40-MCS5	64-QAM	20	5.3	-77
HE40-MCS6	64-QAM	19	5	-75
HE40-MCS7	64-QAM	19	5	-73
HE40-MCS8	256-QAM	18	5	-70
HE40-MCS9	256-QAM	18	5	-68
HE40-MCS10	1024-QAM	17	5	-65
HE40-MCS11	1024-QAM	17	5	-62
HE40-MCS12	4096-QAM	16	5	-61
HE40-MCS13	4096-QAM	16	5	-60

TX/RX Specification (11ax) – 5180 MHz to 5825 MHz

TX Power per chain (SISO mode), ± 2 dBm.

DC power consumption is the total dc power drawn only by the miniPCle module in 2x2 MIMO mode and it excludes the dc power drawn by the main board to which the module is connected.

RX Sensitivity per chain (SISO mode), ± 2 dBm.

Data Rate	Modulation	TX Power (dBm)	DC Power Consumption (Watts)	RX Sensitivity (dBm)
HE20-MCS0	BPSK	27	9.5	-93
HE20-MCS1	QPSK	27	9.5	-92
HE20-MCS2	QPSK	25	7	-90
HE20-MCS3	16-QAM	24	6.7	-88
HE20-MCS4	16-QAM	23	6.3	-84
HE20-MCS5	64-QAM	22	6	-80
HE20-MCS6	64-QAM	21	5.7	-78
HE20-MCS7	64-QAM	21	5.7	-76
HE20-MCS8	256-QAM	20	5.3	-73
HE20-MCS9	256-QAM	20	5.3	-71
HE20-MCS10	1024-QAM	19	5	-68
HE20-MCS11	1024-QAM	19	5	-65
HE20-MCS12	4096-QAM	18	5	-64
HE20-MCS13	4096-QAM	18	5	-63
HE40-MCS0	BPSK	27	9.5	-90
HE40-MCS1	QPSK	27	9.5	-89
HE40-MCS2	QPSK	25	7	-87
HE40-MCS3	16-QAM	24	6.7	-85
HE40-MCS4	16-QAM	23	6.3	-81
HE40-MCS5	64-QAM	23	6.3	-77
HE40-MCS6	64-QAM	22	6	-75
HE40-MCS7	64-QAM	21	5.7	-73
HE40-MCS8	256-QAM	20	5.3	-70
HE40-MCS9	256-QAM	20	5.3	-68
HE40-MCS10	1024-QAM	19	5	-65
HE40-MCS11	1024-QAM	19	5	-62
HE40-MCS12	4096-QAM	18	5	-61
HE40-MCS13	4096-QAM	18	5	-60

TX/RX Specification (11ax) – 5180 MHz to 5825 MHz

TX Power per chain (SISO mode), ± 2 dBm.

DC power consumption is the total dc power drawn only by the miniPCle module in 2x2 MIMO mode and it excludes the dc power drawn by the main board to which the module is connected.

RX Sensitivity per chain (SISO mode), ± 2 dBm.

Data Rate	Modulation	TX Power (dBm)	DC Power Consumption (Watts)	RX Sensitivity (dBm)
HE80-MCS0	BPSK	27	9.5	-87
HE80-MCS1	QPSK	27	9.5	-86
HE80-MCS2	QPSK	25	7	-84
HE80-MCS3	16-QAM	24	6.7	-82
HE80-MCS4	16-QAM	23	6.3	-78
HE80-MCS5	64-QAM	22	6	-74
HE80-MCS6	64-QAM	21	5.7	-72
HE80-MCS7	64-QAM	21	5.7	-70
HE80-MCS8	256-QAM	20	5.3	-67
HE80-MCS9	256-QAM	19	5	-65
HE80-MCS10	1024-QAM	19	5	-62
HE80-MCS11	1024-QAM	19	5	-59
HE80-MCS12	4096-QAM	18	5	-58
HE80-MCS13	4096-QAM	18	5	-57
HE160-MCS0	BPSK	27	9.5	-84
HE160-MCS1	QPSK	26	9	-83
HE160-MCS2	QPSK	24	6.7	-81
HE160-MCS3	16-QAM	23	6.3	-79
HE160-MCS4	16-QAM	22	6	-75
HE160-MCS5	64-QAM	22	6	-71
HE160-MCS6	64-QAM	21	5.7	-69
HE160-MCS7	64-QAM	20	5.3	-67
HE160-MCS8	256-QAM	20	5.3	-64
HE160-MCS9	256-QAM	19	5	-62
HE160-MCS10	1024-QAM	18	5	-59
HE160-MCS11	1024-QAM	18	5	-56
HE160-MCS12	4096-QAM	17	5	-55
HE160-MCS13	4096-QAM	17	5	-54

TX Specification


Parameter	Specification
RF Power control Step	0.5 dBm
Spectral Mask Compliance	Compliant with IEEE 802.11an/ac/ax Mask, with > 5 dB margin
EVM Compliance	Compliant with IEEE 802.11a/n/ac/ax EVM requirement with > 5 dB margin
Second Harmonic Spurious Emission	-60 dBC
Third Harmonic Spurious Emission	-70 dBC
Transmitter Spurious Emission	FCC PART 15E COMPLIANT

RX Specification

Parameter	Specification
Receiver Maximum input level (10% PER)	
11a < 18 Mbps, 11n/11ac/11ax < MCS5	> 2 dBm
11a > 18 Mbps, 11n/11ac/11ax > MCS5	> -10 dBm
Frequency Accuracy	Within ± 10 PPM
Receiver Adjacent Channel Rejection (ACR)	
11n, 6 Mbps	> 25 dBC
11ac VHT40, 11ax HE80-MCS0	> 30 dBC
11ax, HE160-MCS11	> 11 dBC
Interference De-sensitization 11ax, HE20-MCS13	
400 MHz to 2350 MHz	> 70 dBC
2400 MHz to 3600 MHz	> 40 dBC
In Band Interference	> 30 dBC


TX EVM PERFORMANCE

Frequency = 4920 MHz, TX Power=18 dBm, IEEE 802.11ax, HE20, MCS11




TX EVM PERFORMANCE

Frequency = 5775 MHz, TX Power = 21 dBm, IEEE 802.11ax, HE20, MCS11




Receiver Interference Desensitization



Receiver Dynamic Range


Rx Dynamic Range-SISO-BW20-11ax-MCS13



MINIPCIE (GOLD FINGER) PIN-OUT

Pin#	Description
1	WAKE_L
2	3.3V
3	RESERVED (NC)
5	RESERVED (NC)
6	1.5V (NC)
7	CLKREQ_L, connected to GND through a pull-down resistor of 0 Ohms.
8	UIM_PWR (NC)
10	UIM_DATA (NC)
11	REFCLK-
12	UIM-CLK (NC)
13	REFCLK+
14	UIM-RESET (NC)
16	UIM_VPP (NC)
17	UIM_C8 (NC)
19	UIM_C4 (NC)
20	W_DISABLE_L (Pulled up to 3.3V)
22	RESET
23	PERN0
24	3.3VAUX (NC)
25	PERP0
28	1.5V (NC)
30	SMB_CLK (NC)
31	PETN0
32	SMB_DATA(NC)
33	PETP0
36	USB_D- (NC)
37	RESERVED (NC)
38	USB_D+ (NC)
39	3.3V
41	3.3V
42	LED_WWAN_L (NC)
44	LED_WLAN_L (NC)
45	5V (FOR PA)
46	LED_WPAN_L (NC)
47	5V (FOR PA)
48	1.5V (NC)
49	5V (FOR PA)
51	5V (FOR PA)
52	3.3V
4,9,15,18,21,26,27,29,34,35,40,43,50	GND

NC- NO CONNECTION

MECHANICAL DIMENSIONS**Trademarks**

The information in this document is being provided in connection with Vizmonet products, which are subject to continuous developments and improvements. While every effort is made to ensure that the information contained in this document is correct and accurate at the time of this printing, Vizmonet makes no representations or warranties with respect to the accuracy of the information and is not liable for errors or mistakes that may arise. However, Vizmonet reserves the right to make changes to specifications and product descriptions at any time without notice. Vizmonet does not assume any responsibility for the use of the described product; neither does it convey any license under its patent rights, or the rights of others. Vizmonet products are not intended, authorized, or warranted for use as components in applications intended to support or sustain life. Built-to-Customize™ is a trademark of Vizmonet. All other trademarks, registered trademarks and product names are the sole property of their respective owners.

Contact

Web: <https://vizmonet.com>
Email: enquiry@vizmonet.com

Headquarters

Vizmonet Pte Ltd
21, Woodlands Close
#03-01, Primz Biz Hub
Singapore 737 854

HW REV#
axE24950.0200